



# Silspec 900 Component A

## SAFETY DATA SHEET

### 1. GENERAL INFORMATION

Product name: Silspec 900 – Component A  
Manufacturer: Silicone Specialties, Inc.  
430 South Rockford  
Tulsa, OK 74120  
918-587-5567  
918-582-7510 FAX  
www.ssicm.com

Emergency Contact# CHEMTREC U.S.: 800-424-9300 International: +1 703-741-5970

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

<u>Health Hazard</u>	<u>Category</u>
Skin Irritation	2
Eye Irritation	2A
Skin Sensitization	1
Aquatic Chronic	2

Signal Word: **WARNING**



#### Hazard Statements

H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H411: Toxic to aquatic life with long lasting effects.

#### Precautionary Statements

Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves.  
Wear eye protection / face protection.  
Avoid release to the environment.  
If on skin: Wash with plenty of water.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Specific treatment (see on this label).  
Wash contaminated clothing before reuse.



# Silspec 900 Component A

## SAFETY DATA SHEET

Collect spillage.  
Take off contaminated clothing and wash it before reuse.

### Hazards not Otherwise Classified

Severe Eye Irritant  
Skin Irritant  
May Cause Sensitization by Skin Contact

### 3. COMPOSITION/INGREDIENT INFORMATION

Ingredients:

Cas#	Chemical Name	%	OSHA PEL	ACGUH TLV
Part A				
25085-99-8	Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	>80%	NE	NA
68609-97-2	Aliphatic Glycidyl Ether	<20%	NE	NE

None of the remaining components are considered a hazardous material or carcinogen (1910.1200 Hazard Communication (d) 4).

### 4. FIRST AID MEASURES

General Advice: Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped trained personnel should begin cardiopulmonary resuscitation immediately.

Inhalation: Supply fresh air and call a doctor.

Skin Contact: Immediately wash with water and soap and rinse thoroughly.

Eye Contact: Rinse opened eyes for several minutes under running water. If symptoms persist, consult a doctor.

Ingestion: Drink copious amounts of water and provide fresh air. Immediately call a doctor. Should vomiting occur, turn victim's head to the side. Be sure to keep victim's head below hips to avoid aspiration of vomit into the lungs.

### 5. FIRE FIGHTING MEASURES

Special Fire Fighting Procedures: NFPA Class B-C extinguisher (dry chemical or foam) for Class 1C fires. Water spray may be ineffective on fire but can protect fire-fighters and cool closed containers. Use fog nozzles if water is used. Use supplied breathing masks.

Protection of Firefighters: Fire may produce irritating, corrosive and/or toxic gases. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces SCBA. Structural firefighters protective clothing will only provide limited protection.

### 6. ACCIDENTAL RELEASE MEASURES

Personal Protective Equipment: Splash Goggles, Gloves, Apron



# Silspec 900 Component A

## SAFETY DATA SHEET

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Follow facility/company's emergency plans.

**Small Spills:** Absorb with an inert material (sand, vermiculite). Sweep or scoop up and put into disposal containers. Flush area immediately with water (prevent water from entering waterways).

**Large Spills:** Dike area far ahead of liquid spill for later disposal. Do not release into sewers or waterways. Absorb with an inert material (sand, vermiculite). Sweep or scoop up into disposal containers. Flush area immediately with water (prevent water from entering waterways)

**Regulatory Requirements:** Follow applicable OSHA regulations (29 CFR 1910.120). Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area or until spill clean-up has been completed.

### **7. HANDLING AND STORAGE**

**Handling Precautions:** For professional use only. Avoid eye/skin contact. Wash after using and before eating or smoking. Use as directed. Avoid uncontrolled mixing with other mixtures (strong acids, bases and oxidizers).

**Storage Requirements:** Store in cool/dry location. Do not allow material to freeze, as product may be damaged. Do not handle, store or open near an open flame, sources of heat or sources of ignition.

### **8. EXPOSURE CONTROL AND PERSONAL PROTECTION**

HMIS PP, H | Splash Goggles, Gloves, Apron

**VENTILATION:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs. Local exhaust ventilation is preferred because it prevents containment dispersion into the work area controlling it as its source.

**RESPIRATORY PROTECTION:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and if necessary, wear OSHA/NIOSH approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen.

**PROTECTIVE CLOTHING/EQUIPMENT:** Wear chemically protective gloves, boots and aprons to prevent prolonged or repeated skin contact. Wear protective goggles and face shield, per OSHA eye and face protection (29 CFR 1910.133).

**CONTAMINATED EQUIPMENT:** Separate contaminated work clothing from street clothing. Launder before reuse. Remove this material from your work shoes and clean personal protective equipment.

**OTHER PRECAUTIONS:** Never eat, drink or smoke in work areas.

This material is not listed by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.



# Silspec 900 Component A

## SAFETY DATA SHEET

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear to light amber
Physical State	Liquid
Boiling Point:	ND
Odor:	Mild
Freezing/Melting Point:	ND/NE
pH:	ND
Solubility:	Insoluble
Vapor Pressure:	NE
Vapor Density:	(Air = 1) > 1
Spec Grav./Density:	1.19
VOC:	0
Evap Rate:	Slower than Butyl Acetate
Viscosity:	Brookfield 500 cps
Percent Volatile:	0
Flash Point:	>200° F
Flash Point Method:	Pensky Martens Closed Cup
Burning Rate:	No data available
Autoignition Temp:	No data available

### 10. STABILITY AND REACTIVITY

Stability:	Stable
Conditions to Avoid:	None
Materials to Avoid:	Strong oxidizers, acids and bases
Hazardous Decomposition Products:	CO, CO <sub>2</sub> , NO <sub>x</sub>
Hazardous Polymerization:	None

### 11. TOXICOLOGICAL INFORMATION

LD50 and LC50 Data: Not available  
Skin Corrosion/Irritation: Causes skin irritation.  
Serious Eye Damage/Irritation: Causes serious eye irritation.  
Respiratory or Skin Sensitization: May cause an allergic skin reaction.  
Germ Cell Mutagenicity: Not classified  
Acute Toxicity: Not classified  
Teratogenicity: Not available  
Carcinogenicity: Not classified  
Specific Target Organ Toxicity (Repeated Exposure): Not classified  
Reproductive Toxicity: Not classified  
Specific Target Organ Toxicity (Single Exposure): Not classified  
Aspiration Hazard: Not classified  
Symptoms/Injuries After Inhalation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Symptoms/Injuries After Skin Contact: Exposure may produce an allergic reaction.  
Symptoms/Injuries After Eye Contact: Causes serious eye irritation.  
Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.  
This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater.



# Silspec 900 Component A

## SAFETY DATA SHEET

### 12. ECOLOGICAL INFORMATION

Aquatic toxicity                      Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.  
Toxicity to other organisms:      No data available

### 13. DISPOSAL CONSIDERATIONS

When disposed of properly, this material does not meet RCRA classification or listing for hazardous waste. Never dispose of a liquid to a landfill. Spilled material should be stabilized or solidified prior to disposal. Once stabilized/solidified, the material may be disposed of through normal means. Certain localities and state laws have specific disposal requirements for non-hazardous industrial chemicals. Consult local municipal authorities, landfill personnel, disposal companies for details prior to any disposal activity. Always follow local, state and federal regulations.

### 14. TRANSPORT INFORMATION

DOT, ADG: Not regulated for transport\*.

IMDG: Not regulated for transport\*. For single or inner packagings greater than 5L: UN 3082 Environmentally Hazardous Substances, Liquid, n.o.s. (epoxy resin), Marine Pollutant, 9 III

IATA: Not regulated for transport\*. Non-bulk packagings (<119 Gal) are excepted from being classed as a Marine Pollutant per 49 CFR 171.4(c)(2), IATA DGR Special Provision A197.

TDG: Not regulated for transport\*. This product meets the specifications set forth by Special Provision 99. For bulk packagings (>119 gallons): UN 3082 Environmentally Hazardous Substances, Liquid, n.o.s. (epoxy resin), Marine Pollutant, 9 III

\*In quantities not to exceed 5kg/5L per single or inner packaging, marine pollutants are not subject to regulation by ground, air, or vessel. See 49 CFR 171.4(c)(2), IATA DGR Special Provision A197, and IMDG Code 2.10.2.7

### 15. REGULATORY INFORMATION

This product is not hazardous.

**State Regulations** This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

### 16. OTHER INFORMATION

Rating Scale: 0-4

HMIS II ratings:                      Health = 1, Fire = 1, Reactivity = 0  
HMIS III ratings:                     Health = 1, Fire = 1, Physical Hazard = 0  
NFPA ratings:                         Health = 1, Fire = 1, Reactivity = 0



# Silspec 900 Component A

## SAFETY DATA SHEET

### **DISCLAIMER**

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

User Responsibility: The information in this document cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions, in addition to those described herein, are required. Any health hazard and safety information herein should be distributed to customers or

The information contained herein is, to the best of our knowledge and belief, accurate and current as of the date of this SDS. However, since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representation or warranties, either expressed or implied, as to its correctness or completeness, or as of merchantability, fitness for a particular purpose, or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers or as to the results or reliance of this product. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.